



Anti Slip Solutions Ltd
Bridge House, Severn Bridge, Riverside North
Bewdley, Worcs., DY12 1AB ENGLAND
Tel: +44 (0) 1299 406011
Fax: +44 (0) 1299 406023
e-mail: info@safe-grip.co.uk
www.safe-grip.co.uk

GENERAL INFORMATION - FLOORS

- 1) **Safe Grip** is designed to improve the slip resistance of hard porous surfaces that become slippery when moist or wet. The product is ideally suited for application to Ceramic, Marble, Terracotta and Terrazzo tiles; traditional Terrazzo floors, granite, stone, concrete and similar types of materials.
- 2) **Safe Grip** ***SHOULD NOT*** be applied to plastic, wood, acrylic, epoxy, polyurethane, vinyl, linoleum, glass and similar types of products.
- 3) **If in doubt please consult the company for advice before applying the product.**
- 4) In all cases a small test area of **Safe Grip** should be applied to establish the length of time required to produce the desired level of slip resistance.
- 5) Generally most surfaces will reach a satisfactory level of slip resistance with one application of **Safe Grip** after an exposure period of between 8 and 12 minutes. Very hard and dense materials may require additional applications.
- 6) **IMPORTANT:** In all cases do not allow the **Safe Grip** product to dry out on the surface being treated.

7) APPLICATION:

- A: Thoroughly clean & rinse the surface to be treated and dry off all surface water. The surface to receive the treatment should preferably be dry but may be a little damp. However, the surface must be free of standing water.
- B: Spread the **Safe Grip** liberally and evenly using a brush mop or sponge and allow to stand for the selected period of time. Agitate periodically during the activation period.
- C: At the end of the treatment period rinse off with clean water, the area is now ready for immediate use.

8) PACKAGING & COVERAGE:

Safe Grip is supplied in five container sizes, 250ml and 500ml bottles and 1 litre, 2.5 litre and 5 litre jugs. The containers are fitted with screw caps to facilitate good storage conditions for unused product.

Consumption will be determined by the type of surface being treated and the number of applications required. Generally 1 litre of **Safe Grip** will be required to treat between 10 m² & 15 m² of floor surface.

9) HEALTH & SAFETY:

At all times applicators should wear appropriate safety clothing and maintain good standards of hygiene. Please consult the Material Safety Data Sheet for detailed advice on handling this product

SAFE GRIP SERIOUSLY REDUCES THE RISK OF SLIPPING